

Electrical Specifications



• Frequency Range	2.4 – 2.5 GHz
• Gain	15 dBi
• Polarization	Dual Linear (V and H)
• Horizontal Beamwidth	100° (-6 dB)
• Vertical Beamwidth	9° (-3 dB)
• VSWR	2 (Max.)
• Front-to-back Ratio	-23 dB (Max.)
• Isolation	25 dB (Min.)
• Impedance	50 Ω
• Lightning Protection	DC Ground

Environmental and Mechanical Specifications

• Temperature	-40 °C to +60 °C
• Humidity	5 - 95% (Non-Condensing)
• Wind Loading	Up to 216 km/h (134 mph)
• Radome Color	Gray
• Radome Material	ABS, UV Resistant
• Weight	2.5 kg
• Dimensions	700 x 140 x 50 mm
• Connector	2 x RP-SMA
• Mechanical Downtilt	+10/-3° (Max.)




Mounting Scenario



Mounting for C1xn+



Antenna Mounting Kit



Product Ordering Information

2.4 GHz 15 dBi Sector Antenna (Part No.: SD.AN-2S15-01)

- C1xn+ Mounting Bracket
- 2 x RF Cable
- Pole Mount Accessories

Contact Us

- Email: sales@altaitechnologies.com

Although Altai has attempted to provide accurate information in these materials, Altai assumes no legal liability for the accuracy and completeness of the information. All specifications are subject to change without notice.