



Product Overview

Altai BX700-S is a cost-effective Point-to-Multipoint (PtMP) base station with an advanced beamforming antenna. It provides best-in-class radio interference mitigation and wide coverage, superior to any Access Point with a horn or uplink-only beamforming antenna.

The BX700-S is the only PtMP base station in its price range that supports an integrated bi-directional (uplink and downlink) beamforming antenna, enabling full network deployment with just two frequency channels.

Offering 750 Mbps over a 90° sector, Altai BX700-S ensures revenue growth with lowest TCO and minimum spectrum usage, while delivering fiber-like residential services.

Product Highlights

- » Advanced beamforming antenna
- » Up to 750 Mbps, 3 Gbps per 4 sectors
- » Best-in-class interference immunity
- » Frequency reuse – 2 per network
- » Best effort class of service
- » Built-in GPS
- » WAN connectivity over SFP
- » 5 GHz band

Architecture

- Outdoor base station with integrated smart beamforming antenna and built-in GPS

Network Interface

- Data Interface: 1 x 1 GE RJ45 Port with PoE PD
1 x 1 Gbps SFP
- PoE and ODU Interfaces: Outdoor CAT-5e; Maximum Cable Length: 75m for 1000Base-T

Radio

- Wireless Topology: PtMP Base Station
- Maximum Capacity: 750 Mbps Net Aggregate Throughput
- Maximum Subscriber Units: Up to 64
- Range: Up to 40 km
- Frequency: 4900 MHz – 5990 MHz *
- Channel Bandwidth: Configurable: 10, 20, 40, 80 MHz *
- Dynamic Bandwidth Selection: 20/40/80 MHz
- Modulation: OFDM (BPSK/QPSK/16QAM/64QAM/256 QAM)
- Error Correction: FEC k = 1/2, 2/3, 3/4, 5/6
- Adaptive Modulation/Coding: Supported
- Duplex Technology: TDD
- DFS: Supported *
- Diversity: Supported
- Antenna Modes: MIMO 2x2, Diversity, Adaptive MIMO/Diversity
- Dynamic Bandwidth Mgmt.: Best Effort Service Level
- Maximum TX Power: 25 dBm *
- Encryption: AES128
- TDD Synchronization: Supported via Built-in GPS Receiver
- Uplink/Downlink Allocation: Configurable: Symmetric or Asymmetric

Antenna

- Integrated Antenna
- Gain: 17 dBi
- VSWR: 2.0: 1
- 3 dB Azimuth Beamwidth: 24° (Typical) Steered over 90 ° Sector
- 3 dB Elevation Beamwidth: 12° (Typical)
- Polarization: Dual Linear (Vertical and Horizontal)
- Sidelobes Level: -18 dB (Typical)
- Cross Polarization: -30 dB (Typical)
- F/B Ratio: 30 dB
- Port-to-Port Isolation: 35 dB (Typical)
- Lightning Protection: DC Grounded

Networking

- Sub Convergence Layer: Layer 2, Bridging Learning of 8K MAC Addresses
- QoS: Packet Classification to 4 Priority Queues according to 802.1P or Diffserv
- VLAN Support: 802.1Q, QinQ, 4094 VLANs
- MTU Size: Up to 9216 bytes
- ODU Management: IPv4/IPv6 Dual-Stack; SNMPv1, SNMPv3; HTTP/HTTPS using Web Browser
- 802.1x: Supported
- Option 82: Supported
- DHCP Filtering: Supported
- IGMP Snooping: Supported
- PPPoE Filtering: Supported
- RADIUS Authorization: Supported
- RADIUS User Authentication: Supported
- Syslog: Supported

Physical Specification

- Dimension: 325 (w) x 340 (h) x 90 (d) mm
- Weight: 3.25 kg

Power Supply

- Power Consumption: < 25W
- Power Feeding: Power provided over ODU-IDU Cable
- PoE Nominal Voltage: 55V

Environmental Specification

- Operating Temperature: -35 °C to 60 °C
- Humidity: 100% Condensing
- Enclosure Protection: IP67 per EN/IEC 60529, NEMA Type 4 Enclosure

Regulatory Compliance

Radio

- USA: FCC 47CFR Part 15.407
- EU: ETSI EN 301 893; ETSI 302 502

Safety

- USA: UL/CSA-C22.2 62368-1, UL/CSA-C22.2 60950-22
- EU: EN/IEC 62368-1, EN/IEC 60950-22

EMC

- USA: FCC 47CFR Part 15 Subpart B, Class B
- EU: ETSI EN 301 489-1, ETSI EN 301 489-4, ETSI 301 489-17

Product Ordering Information

BX700-S (Part No.: AT-5AG5-9854)

- BX700-S PtMP Base Station
- Mounting Kit
- IP67 Cable Glands

Optional Accessories

- PoE Injector with DC Input 10VDC – 60VDC
- PoE Injector with AC Input 100VAC – 240VAC

Contact Us

- Email: sales@altaitechnologies.com

BX700S-PB-20220607

** May be limited by regulation*

Although Altai has attempted to provide accurate information in these materials, Altai assumes no legal liability for the accuracy and completeness of the information. All specifications are subject to change without notice.